

# BETON ÇELİK ÇUBUKLARI / HOT ROLLED ROUND STEEL

(Nervürlü / Ribbed)



## BOYUT STANDARDI / DIMENSION STANDARD


TS 708

DIN 488

## KALİTE STANDARDI / QUALITY STANDARD

TS 708

Anma çapı Nominal diameter (d)	Anma kütlesi Nominal weight (Kg/m)	Kesit alanı Section area mm <sup>2</sup>
8	0,395	50,3
10	0,617	78,5
12	0,888	113,0
14	1,210	154,0
16	1,580	201,0
18	2,000	254,4
20	2,470	314,0
22	2,985	380,0
25	3,850	491,0
26	4,168	531,0
28	4,830	616,0
30	5,550	706,5
32	6,310	804,0
40	9,860	1256,0



Nervür Çapı Rib diameter (d)	Max. a <sub>1</sub>	b <sub>1</sub>	Max. b <sub>2</sub>	a <sub>11</sub>	C
8	0,8	0,8±0,32	0,8	0,4-0,8	0,5-8
10	1,0	1,0±0,40	1,0	0,5-1,0	0,5-10
12	1,2	1,2±0,48	1,2	0,6-1,2	0,5-12
14	1,4	1,4±0,56	1,4	0,7-1,4	0,5-14
16	1,6	1,6±0,64	1,6	0,8-1,6	0,5-16
18	1,8	1,8±0,72	1,8	0,9-1,8	0,5-18
20	2,0	2,0±0,80	2,0	1,0-2,0	0,5-20
22	2,2	2,2±0,88	2,2	1,1-2,2	0,5-22
25	2,5	2,5±1,00	2,5	1,25-2,5	0,5-25
26	2,6	2,6±1,04	2,6	1,30-2,6	0,5-26
28	2,8	2,8±1,12	2,8	1,40-2,8	0,5-28
30	3,0	3,0±1,2	3,0	1,50-3,0	0,5-30
32	3,2	3,2±1,28	3,2	1,60-3,2	0,5-32
40	4,0	4,0±1,60	4,0	2,00-4,0	0,5-40